



## ATH-M30x

With enhanced audio clarity and sound isolation, the **ATH-M30x** professional monitor headphones are tuned for highly detailed audio. Featuring strong mid-range definition, these versatile monitoring headphones are ideal in a variety of situations. Designed primarily for studio tracking and mixing, they offer added features for increased portability, making them a great choice for field recording.

- **Advanced build quality and engineering**
- **40 mm drivers with rare earth magnets and copper-clad aluminum wire voice coils**
- **Tuned for enhanced detail, with excellent mid-range definition**
- **Circumaural design contours around the ears for excellent sound isolation in loud environments**
- **Convenient single-side cable exit**

|                             |                                   |
|-----------------------------|-----------------------------------|
| <b>Driver</b>               | 40 mm                             |
| <b>Magnet</b>               | Neodymium                         |
| <b>Voice Coil</b>           | CCAW (Copper-clad aluminum wire)  |
| <b>Frequency Response</b>   | 15 – 22,000 Hz                    |
| <b>Maximum Input Power</b>  | 1,300 mW at 1 kHz                 |
| <b>Sensitivity</b>          | 96 dB                             |
| <b>Impedance</b>            | 47 ohms                           |
| <b>Cable</b>                | 3.0 m, left-side exit             |
| <b>Weight</b>               | 220 g without cable and connector |
| <b>Included Accessories</b> | 6.3 mm screw-on adapter, pouch    |



## ATH-M20x

The **ATH-M20x** professional monitor headphones are a great introduction to the critically acclaimed M-Series line. Modern design and high-quality materials combine to deliver a comfortable listening experience, with enhanced audio and effective isolation. An excellent choice for tracking and mixing.

- **Advanced build quality and engineering**
- **40 mm drivers with rare earth magnets and copper-clad aluminum wire voice coils**
- **Tuned for enhanced low-frequency performance**
- **Circumaural design contours around the ears for excellent sound isolation in loud environments**
- **Convenient single-side cable exit**

|                             |                                   |
|-----------------------------|-----------------------------------|
| <b>Driver</b>               | 40 mm                             |
| <b>Magnet</b>               | Neodymium                         |
| <b>Voice Coil</b>           | CCAW (Copper-clad aluminum wire)  |
| <b>Frequency Response</b>   | 15 – 20,000 Hz                    |
| <b>Maximum Input Power</b>  | 700 mW at 1 kHz                   |
| <b>Sensitivity</b>          | 96 dB                             |
| <b>Impedance</b>            | 47 ohms                           |
| <b>Cable</b>                | 3.0 m, left-side exit             |
| <b>Weight</b>               | 190 g without cable and connector |
| <b>Included Accessories</b> | 6.3 mm snap-on adapter            |